

Mobil Zerice S Series

Refrigeration Compressor Lubricants

Product Description

Mobil Zerice S Oils are premium quality synthetic refrigeration compressor lubricants. Based on alkyl benzenes, which due to their nature, have superior miscibility with hydrochlorofluorocarbon (R22), as well as chlorofluorocarbon refrigerants (R 502 & R 12: possibly used on some old refrigerating plants). This allows them to be used in very low temperature applications, down to -60C.

Features & Benefits

Relative to mineral and other synthetic lubricants, Mobil Zerice S has superior solubility with halocarbon refrigerants. This helps avoid the common problem of oil separation and congealing on the valve and heat transfer surfaces of the refrigeration system.

Additionally, Mobil Zerice S lubricants have very low pour and floc points which helps prevent harmful wax precipitation that can block expansion valves and heat transfer surfaces.

Mobil Zerice S lubricant's synthetic nature provides excellent chemical stability and resists reaction with refrigerants and high thermal stability which helps prevent oil breakdown.

Features	Advantages and Potential Benefits
Miscibility with halocarbon refrigerants	Increased system efficiency
Low pour and floc points	Avoids wax precipitation and increased system efficiency
Chemical Stability	Long oil service life

Applications

Mobil Zerice S lubricants are recommended for all refrigeration compressor types, reciprocating or rotary screw types. They are well suited for use with fluorocarbon refrigerants. They should not be used with sulfur dioxide or R134A refrigerants. The specific viscosity grade should be selected in accordance with the compressor manufacturer's recommendations.

Health & Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application, following the recommendations provided in the Material Safety Data Sheet (MSDS). MSDSs are available upon request through your sales contract office, or via the Internet on <http://www.exxonmobil.com>. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Typical Properties	Mobil Zerice S 68	Mobil Zerice S 100
Viscosity, ASTM D 445		
cSt @ 40°C	68	100
cSt @ 100°C	6.5	8.0
Pour Point, °C, ASTM D 97	-27	-27
Flash Point, °C, ASTM D 92	174	186
Floc Point, R12, °C	-60	-60
Acid Number, mg/KOH, max., ASTM D 974	.05	.05
Copper Corrosion 3 h, at 100 °C, ASTM D 130	1	1
Water Content, ppm, ASTM D 1533	<50	<30

Due to continual product research and development, the information contained herein is subject to change without notification. Typical properties may vary slightly.

ExxonMobil Marine Limited
Ermyn Way, Leatherhead, Surrey, United Kingdom KT22 8UX
www.exxonmobil.com

© 2004 Exxon Mobil Corporation
The ExxonMobil logotype and Mobilgard are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.