



# AeroShell Compound 07

AeroShell Compound 07 is a de-icing fluid composed of ethylene glycol, isopropyl alcohol and distilled water. Specification DTD.406B requires the product to have the following approximate composition:

Ethenediol (BS.2537) 85% volume

Isopropanol (BS.1595) 5% volume

Distilled water 10% volume

## DESIGNED TO MEET CHALLENGES

### Applications

AeroShell Compound 07 is used for in-flight de-icing of windscreens, propellers, wings, tailplanes, etc. on suitably equipped aircraft.

AeroShell Compound 07 is also recommended for removing hoar frost and light snow/ice from parked aircraft.

AeroShell Compound 07 can be sprayed undiluted or mixed with up to 50% volume of water, depending upon the severity of the icing conditions, the efficiency of the spraying technique and whether it is applied hot or cold.

### Spécifications, Approbations et Recommandations

- DTD.406B (British)
- NATO Code S-745
- Joint Service Designation AL-5

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

### Caractéristiques types

Propriétés	Méthodes	DTD.406B	Typical
Density	@15.5°C kg/l	1.092 to 1.097	1.096
Kinematic Viscosity	@20°C mm <sup>2</sup> /s	11.0 to 13.0	12.8
Cold Test	@-40°C	No Deposition	Complies
pH value		6.0 to 7.5	6.1
Conductivity	micromho/cm	5.0 max	0.1
Miscibility with water	@15°C	Must pass	Passes

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

### Hygiène, Sécurité et Environnement

#### • Health and Safety

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com/>

#### • Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

### Informations complémentaires

#### • Advice



may be obtained from your Shell representative.